

WEATHERPROOF INFRARED DAY & NIGHT COLOR DOME CAMERA

HIGH RESOLUTION

700 TV LINES



Features:

VIDEO

- 700 TV Lines
- 1/3" SONY Super HAD II CCD inside
- Vivid true color video
- Night Blur Control

INFRARED

- BLACK DIAMOND 5mm IR LEDs x 24 units
- Automated ON/OFF design IR LEDs via smart light sensor - Daylight (Off) / Dark (On)

HOUSING & BRACKET

- Weatherproof rugged rust free aluminium die-cast dome housing
- Heatless design
- 3 -Axis camera adjustment
- Anti IR reflect front glass design (double glass)
- Stylish dome housing

MODEL:

XR4i

Max. 25M Infrared
700 TV Lines
Night Blur Control



BLACK DIAMOND
IR LED
4X brighter

IP65

OUTDOOR/INDOOR

Standard - SERIES



Support Wall & Ceiling
mount installations

FEATURES & FUNCTION

Hi-Resolution 700 TV Lines



Standard resolution 420 TV lines



High resolution 700 TV lines

Built-in Night Blur Control




Normal standard camera



XR4i with Night Blur Control

Dimensions



PRODUCT OVERVIEW

Model: XR4i

Hi-Resolution Weatherproof Infrared Color Dome Camera

- 1/3" SONY CCD
- 700 TV Lines
- Day: 1 Lux / Night: 0 Lux (IR On)
- Max. 25M IR distance (82.5 t..)
- Night Blur Control
- 4mm or 6mm infrared camera lens
- 24 units x BLACK DIAMOND IR LED's
- Aluminium die-cast camera housing
- Anti-IR reflect front glass design
- 3 Axis camera adjustment
- IP65 weatherproof

TECHNICAL SPECIFICATIONS

IMAGE SENSOR	- 1/3" SONY CCD
VIDEO RESOLUTION	- 700 TV Lines
MINIMUM ILLUMINATION	- Day: 1 Lux / Night: 0 Lux (IR On)
INFRARED DISTANCE	- 25 Meters / 82.5 ft.
INFRARED LED	- 24 units x BLACK DIAMOND IR LED's
SYNC SYSTEM	- Internal
WHITE BALANCE	- Auto
GAIN CONTROL	- Auto
SCANNING SYSTEM	- 2:1 interface
S/N RATIO	- More than 48db
ELECTRONIC SHUTTER	- PAL: 1/50 ~ 1/100000 sec.
	- NTSC: 1/60 ~ 1/100000 sec.
IRIS	- AES
CAMERA LENS	- 4mm or 6mm fixed iris infrared lens (M12 tread type)
VIDEO OUTPUT	- Composite 1.0Vp-p at 75 Ohms
OPERATION TEMPERATURE	- 5°C to 60°C
OPERATIONAL HUMIDITY	- Within 85% RH
POWER SUPPLY INPUT	- DC 12 volts
OPERATING CURRENT	- 60mA (IR Off) / 260mA ± 10% (IR On)
CASING CONSTRUCTION	- Aluminium die-cast
FRONT GLASS DESIGN	- Anti IR reflect
CAMERA NETT WEIGHT	- Approx. 400 grams.

Manufactured by:

INOX MANUFACTURING (M) SDN. BHD.

- Malaysia (Company No. 671850-H)

INOX SECURITY PTY. LTD.

- Canada (Incorporation No. BC 0722077)

www.inox.com.my



Authorised Dealer:

Specifications, description and design are subject to change without prior notice.
The brands and products names are properties of their respective owners
Pictures used in this catalog are for illustration purpose only